


MAGNETIC DISPLACEMENT MEASURING INSTRUMENT


磁性位移测量仪

MA10L/MZ10L


- 显示分辨率：10um, 50um, 100um, 1mm
Display resolution : 10um, 50um, 100um, 1mm
- 重复测量精度：Ma x 10um
Repeated measurement accuracy: Max 10 um
- 多功能菜单，可自由设定参数
Multifunctional menu, are free to set parameters
- 高对比度，大屏幕LCD显示
High contrast, large screen LCD display
- 按键/菜单可锁定
Buttons/menu can be locked
- 公制/英制可切换
Metric/inch swappable
- 长度/角度测量模式
Length/Angle measurement model
- 绝对/相对测量模式
Absolute/relative measurement model
- 液晶背光：清晰醒目
LCD backlight: clearly marked
- 非接触式测量，无磨损
Non-contact measurement, no wear and tear
- 防护级别高，抗油污，抗灰尘
High level of protection, oil resistance, resistance to dust
- 更换电池便捷
Replace the battery is convenient
- 卡式外壳，安装便捷
Cassette case, installation is convenient



正视图
Front view



侧视图 1
Side view 1



侧视图 2
Side view 2

特性 features	技术参数 Technical parameters	备注 Notes
测量参数 Measurement parameters		
系统精度 System accuracy	$\pm(0.03+0.01 \cdot L)$ mm	L单位为：米 Unit: m
测量/显示范围 Measurement/display range	-999999~999999	
显示分辨率 Display resolution	0.01/0.05/0.1/1	单位为：毫米 Unit: mm
移动速度 Movement speed	Ma x 5m/s	
结构参数 Structural parameter		
外观尺寸 Outward appearance size	见右图 See right	单位为：毫米 Unit: mm
外壳材料/颜色 Housing material/color	ABS+PC 蓝色、黑色 ABS+PC blue, black	
传感器线长度 Sensor cable length	1米 1 m	可按需订制 Customized on-demand
重量 Weight	约0.4Kg About 0.4Kg	
其他参数 Other parameters		
电源 Power supply	2节AA 1.5V Section 2-AA 1.5V	5号电池 5th battery
适用的磁尺 Applied magnetic ruler	MS 500/5mm	
工作温度 Working temperature	-10°C~+60°C	
储存温度 Storage temperature range	-30°C~+80°C	
防护等级 Protection rating	Ip54前面板 IP67传感器 IP54 front panel an IP67 sensor	
抗震性能 Seismic performance	10g(5~100HZ)	DIN IEC68-2-6
抗冲击性 Impact resistance	30g/15ms	DIN IEC68-2-27

(安装和调试要点，详见产品说明书)

(Installation and commissioning, see product specifications)